



PLASTERERS PREGRIT

Internal Plaster Bonding Agent

Technical Data Sheet



BUILDERS COMPLETE RANGE

Description:

A one part, ready-to-use internal plaster bonding agent with added aggregate to provide a key prior to plastering on smooth surfaces.

Features & Benefits:

- ◆ *Bonding agent for smooth surfaces.*
- ◆ *Contains sand/aggregate to provide plaster key.*
- ◆ *Ready to use, one coat application.*
- ◆ *Perfect for use on smooth substrates.*
- ◆ *Pigmented yellow to identify treated areas.*
- ◆ *Phthalate free formulation.*

Uses

PLASTERERS PREGRIT should be used as a primer/ bonding aid prior to plastering on surfaces such as concrete, plaster and difficult, low or non-porous substrates. For **internal use only**, this product is not suitable for external applications.

Limitations

- Do not dilute.
- Do not exceed a maximum thickness of 25mm for complete render system.
- Do not use in temperatures below +5°C.
- Remove any contamination of product to surrounding surfaces before drying .

Preparation

Thoroughly stir before use. Ensure application temperature is above +5°C and all surfaces are clean, dry and free from any contaminants that may hinder adhesion, including any loose or flaking material. Ensure the background is sound and will support the weight of the plaster.

Application

Do not dilute. We recommend a patch test be carried out on a small inconspicuous area to test compatibility prior to full application. Simply apply one coat using a brush or roller and leave to dry for a minimum of 24 hours before plastering. This product is pigmented pale yellow to identify treated areas. Note: cold or humid conditions will increase drying times.

Cleaning Of Tools

Tools can be cleaned with warm soapy water after use.

Size

5L and 10L recycled plastic tubs.

Coverage

Depending upon surface porosity approx. 4-5m² / litre



Shelf Life

24 months from date of manufacture when stored in unopened tubs.

Storage Conditions

Store in cool, dry conditions in the original sealed container between +5°C and +30°C. Protect from frost and away from direct sunlight.

Disposal Of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations. Any spillages should be mopped up immediately with an inert absorbent material such as sand or sawdust.

Health & Safety

Please refer to separate safety data sheet (SDS) for full handling, use and storage instructions. Keep out of reach of children. It is the user's responsibility to determine suitability for use. If in doubt, contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control.

Specification Summary

Appearance	Pale yellow liquid
Composition	Waterbased polymers
Density	1.22g/cm ³
Viscosity	6,000 - 12,000 cP
Application Temperature	+5°C to +30°C
Tub PCR Content	30%
Commodity Code	3824509000

Product / Order Details

Code	Colour	Size	Barcode	UFI
BDPG05	Pale Yellow	5L	5060021368638	-
BDPG10	Pale Yellow	10L	5060021368621	-



Part of the Bond It Builders Complete Range

Head Office: Unit H4, Premier Way, Lowfields Business Park, Elland, West Yorkshire. HX5 9HF.
Telephone: +44 (0)1422 315300 **Email:** salesuk@bonditgroup.com
EU Office: SISL (Bond It) Ireland Limited, 70 Sir John Rogerson's Quay, Dublin 2. **Tel:** +353 1 960 9411
Website: www.bonditgroup.com

Note: The data presented in this leaflet is in accordance with the present state of our knowledge, but does not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Version 6: Updated 23/07/24
 Supercedes: V5 25/03/21

bond it

An **ASTRAL** Limited Company

