



MULTI-PURPOSE READY MIXED FILLER

Domestic Ready Mixed Filler for Repairs in Plaster, Stone, Brick & Wood

Technical Data Sheet

DECORATORS RANGE



Description:

An all purpose ready mixed filler for repairs inside and out. Gives a crack resistant, smooth, finish that can be sanded, overpainted or stained once dried.

Features & Benefits:

- ♦ Fills cracks and holes.
- ♦ Crack resistant.
- ♦ Excellent grip properties.
- ♦ Can be overpainted or stained for colour matching.
- ♦ Waterbased - solvent-free.
- ♦ Extra smooth finish.
- ♦ For interior and exterior use.

Uses

Bond It MULTI-PURPOSE READY MIXED FILLER fills gaps and holes in plaster, brick, plasterboard, render, stone and wood and most other building materials. Dries to a smooth, crack resistant finish, that can be sanded, over-painted or stained once dried.

Limitations

Not suitable for use on metal or plastic. Do not apply outside if rain is imminent (within 5 hours of application). Do not apply at temperatures below +5°C. Not suitable for repairs subject to constant water immersion. Do not apply in layers of more than 9mm deep. Use Bond It ONE HIT WONDER LIGHTWEIGHT FILLER for deep cavities. For outdoor applications the gaps should be sealed afterwards with an oil based paint (leave filler to dry for 12 hours before applying paint).



Preparation

Ready to use, apply straight from the tub. Prepare surfaces, they must be clean, dry and free from any contamination including dust and grease. Cover nail and screw heads with oil based paint and allow to dry. Make sure an adequate key is provided to gloss painted surfaces.

Application

Stir well prior to use then apply using a spatula or spreader. Press the material firmly into the gap. For deep cavities, apply in layers, allowing each one to dry (approx. 1 hour). Make sure the hole is overfilled to allow for sanding and finish with a wet knife. Once dry, area can be sanded and smoothed. Can be overpainted with most solvent based and emulsion based paints and stains (test suitability before full scale application).



Drying Time

1-8 hours depending on depth and temperature.

Cleaning Of Tools

All tools should be cleaned immediately after use with warm soapy water.

Size

750g plastic tins.

Colour

Off-white paste.

Shelf Life

24 months from date of manufacture when stored in original, sealed tubs.

Storage Conditions

Store in cool, dry conditions in original sealed container between +10 and +20°C. Keep away from direct sunlight and protect from frost.

Disposal Of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers or used material to a central disposal point in accordance with local regulations.

Health & Safety

Please refer to separate safety data sheet (SDS) for full handling, use and storage instructions. Keep out of reach of children. It is the user’s responsibility to determine suitability for use. If in doubt, contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control.

Specification Summary

Appearance	Off white paste
Movement Accommodation	Low - dries hard
Maximum Fill	9mm in one application - layers can be built up
Maximum Width	25mm
Application Temperature	+5°C to +30°C
Full Cure	1-8 hours
Density	Approx 2.0g/cm³
Commodity Code	3214101000

Product / Order Details

Code	Colour	Fill	Barcode	UFI
BDRMF750	Off White	750g	5060021369550	-



Part of the Bond It Decorating Sundries Range

Head Office: Unit H4, Premier Way, Lowfields Business Park, Elland, West Yorkshire. HX5 9HF.
Telephone: +44 (0)1422 315300 **Email:** salesuk@bonditgroup.com
EU Office: SISL (Bond It) Ireland Limited, 70 Sir John Rogerson’s Quay, Dublin 2. **Tel:** +353 1 960 9411
Website: www.bonditgroup.com

Note: The data presented in this leaflet is in accordance with the present state of our knowledge, but does not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Version 4: Updated 26/09/24
Supersedes: V3 15/02/21

