

STAIN BLOCK

Fast Drying Coating for Covering Stains Prior to Painting

Technical Data Sheet

DECORATORS RANGE



Description:

A spray applied xylene and lead free, fast drying, heavily pigmented white paint which permanently blocks stains prior to decorating. CFC Free.

Features & Benefits:

- ♦ Quick drying.
- ♦ Solvent based.
- ♦ Prepares surfaces for decorating.
- ♦ Covers nicotine, ink, crayon and grease.
- ♦ Prevents stains from reappearing.
- ♦ Quick, easy coverage.
- ♦ Can be re-applied after 15 minutes.
- ♦ For interior use.

Uses

Prevents existing stains such as water marks, mould stains, rust, nicotine, grease, soot and ink marks showing through subsequent coatings. Ideal for areas that have been affected by damp, mould, nicotine and grease.

Ensure all surfaces are clean, dry and free from surface grease or oil or any other contaminants that may hinder adhesion. Ensure the source of the stain has been eliminated. Mask off any areas that need protecting from spray and repair any holes, cracks or surface imperfections prior to coating. Not suitable for use on any bitumen surface.

Preparation

Cover surfaces in the application area that do not require protecting with STAIN BLOCK to avoid any overspray.

Application

Where patches of mould have grown, wash areas first with with an appropriate cleaning agent e.g. Bond It MOULD STOP and allow to dry. Remove rust and soot with a wire brush, wash down areas and allow to dry.

1. Ensure good ventilation whilst using this product. Shake can well until mixing ball rattles and continue to shake for a further 1-2 minutes. Shake frequently during use.
2. Spray directly and evenly over stain in a sweeping motion, 20-30 cm away from the stained area. The multi-directional nozzle in the horizontal position will produce a vertical line and vice versa.
3. Apply 2-3 coats dependant on stain. Allow to dry for at least 15 minutes before re-applying. Final decoration can commence approx. 2 hours after application. Note: ambient conditions and porosity of substrate will affect the drying times.
4. Store upright.



Drying Time

Do not apply at temperatures below +10°C or on substrates that have an RH reading of 90% or above.

Normally STAIN BLOCK should be touch dry after 15 minutes. Drying times are dependant on temperature, moisture content of the substrate and the area. In optimum conditions STAIN BLOCK will be ready for redecorating in approx 2 hours.

Coverage

1.5m² depending on application thickness.

Size

400ml aluminium aerosol tin.

Colour

Off white liquid.

Shelf Life

Minimum 24 months from date of manufacture.

Storage Conditions

Store in cool, dry conditions. Pressurised container: protect from sunlight and frost and do not expose to temperatures exceeding +50°C. Always store and transport in vertical position.

Disposal Of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations. Do not pierce or burn canister after use. Spilt material should be mopped up immediately with an absorbent cloth and a suitable solvent cleaner e.g. Bond It uPVC SOLVENT CLEANER.



Health & Safety

Please refer to separate safety data sheet (SDS) for full handling, use and storage instructions. Keep out of reach of children. It is the user’s responsibility to determine suitability for use. If in doubt, contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control.

Specification Summary	
Appearance	Off-white viscous liquid
Flash Point	Less than -40°C
Solubility in Water	Immiscible
Drying Time	15 minutes
VOC Content	690g/L
Commodity Code	3208209000

Product / Order Details				
Code	Colour	Fill	Barcode	UFI
BDSB400	Off white	400ml	5060021369680	-



Part of the Bond It Decorating Sundries Range

Head Office: Unit H4, Premier Way, Lowfields Business Park, Elland, West Yorkshire. HX5 9HF.
Telephone: +44 (0)1422 315300 **Email:** salesuk@bonditgroup.com
EU Office: SISL (Bond It) Ireland Limited, 70 Sir John Rogerson’s Quay, Dublin 2. **Tel:** +353 1 960 9411
Website: www.bonditgroup.com

Note: The data presented in this leaflet is in accordance with the present state of our knowledge, but does not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Version 3: Updated: 27/08/24
Supersedes: V2 14/06/23

