



ALL PURPOSE WOOD FILLER

1-Part All Purpose Ready Mixed Waterproof Wood Filler

Technical Data Sheet



DECORATORS RANGE

Description:

An easy to use, ready mixed, high quality, solvent-free filler, ideal for filling small imperfections (max 5mm depth) and covering the recesses left by nails and screws in wood.

Features & Benefits:

- ♦ Ready mixed.
- ♦ Can be stained, painted, varnished or dyed once cured.
- ♦ Solvent-free.
- ♦ Flexes with the natural wood.
- ♦ Fills up to 5mm gaps.
- ♦ Low odour and non-flammable.
- ♦ Suitable for internal and external applications.

Uses

General wood filling of windowsills, frames, banisters, MDF and laminates, etc. Repairing wood damaged by wet rot in both internal and external locations. Repair damage and chips to parquet or laminate flooring, wooden furniture, etc.

Limitations

For outdoor applications the cured filler must be sealed with an oil based paint (leave filler to dry for 12 hours before applying paint). As the filler may absorb some stains at different rates to the surrounding timber, always test a small area first. Note: filler may dry darker. Do not exceed 5mm in one coat. For holes deeper than 5mm or for areas subject to impact such as doors and window frames, use Bond It 2 PART WOOD FILLER. Protect from rain when used externally for at least 5 hours. Do not apply below +5°C.



layers allowing each layer to dry. Leave slightly proud and when completely dry, sand down. Drying time touch dry in 30 minutes. When over painting, staining or varnishing, you may get a colour difference with the surrounding wood, so always check on a small area first. Do not add stain to Bond It ALL PURPOSE WOOD FILLER. Not suitable for filling gaps between floor boards.

Cleaning Of Tools

All tools should be cleaned immediately after use with warm soapy water.

Size

250ml plastic tubs.

Colour

Available in 5 colours pine, white, light oak, dark oak.

Shelf Life

24 months from date of manufacture when stored in original, sealed containers.

Storage Conditions

Store in cool, dry conditions in original sealed container between +10 and +20°C. Keep away from direct sunlight. Protect from frost and direct sunlight.

Disposal Of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers or used material to a central disposal point in accordance with local regulations.

Preparation

Ensure the repair area is clean and dry and free from dust or any contamination that may affect adhesion. Cover any nail and screw heads with an oil based paint and allow to dry. Wet down the surfaces that the material is to be applied to. Note: If you intend to over stain the repair, choose the filler colour closest to the wood you are filling, not the stain you intend to use. Always check the stain on a small area as the filler may absorb the stain at a different rate to the wood. As the filler may absorb some stains at different rates to the surrounding timber, always test a small area first.

Application

Stir well before use. Apply with a wetted filling knife or spreader, forcing into cracks and holes. For deep holes, build up in

Health & Safety

Please refer to separate safety data sheet (SDS) for full handling, use and storage instructions. Keep out of reach of children. It is the user’s responsibility to determine suitability for use. If in doubt, contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control.



Specification Summary

Consistency	Waterbased paste
Touch Dry	Approx. 30 minutes dependant on ambient conditions
Density	~ 1.8 g/cm³
Working Temperature	+5°C to +30°C. (Optimum 20°C)
Temperature Resistance	-20°C to +50°C
Commodity Code	3214101000

Product / Order Details

Code	Colour	Size	Barcode	UFI
BDWF1PN	Pine	250ml	5056437400284	-
BDWF1WH	White	250ml	5056437400277	-
BDWF1LO	Light oak	250ml	5056437400291	-
BDWF1TK	Teak	250ml	5056437400567	-
BDWF1DO	Dark Oak	250ml	5056437400550	-



Part of the Bond It Decorating Sundries Range

Head Office: Unit H4, Premier Way, Lowfields Business Park, Elland, West Yorkshire. HX5 9HF.
Telephone: +44 (0)1422 315300 **Email:** salesuk@bonditgroup.com
EU Office: SISL (Bond It) Ireland Limited, 70 Sir John Rogerson's Quay, Dublin 2. **Tel:** +353 1 960 9411
Website: www.bonditgroup.com

Note: The data presented in this leaflet is in accordance with the present state of our knowledge, but does not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Version 6: Updated 26/09/24
Supersedes: V5 25/05/22

