

# weberfix plus

A high performance, ready-mixed ceramic wall tile adhesive for interior use

- Sets in 24 hours
- High initial grab

## About this product

**weberfix plus** is a high performance, acrylic, ready-mixed, thin bed ceramic wall tile adhesive for interior use, designed to be non-slip.

## Features and benefits

- Manufactured under BSI Quality Assurance Scheme ISO 9001
- Thixotropic for ease of spreading
- Zero slip, even with thicker tiles
- Low colour formulation
- Very high initial grab
- Suitable for ceramic tiles up to 300 x 300mm

## Uses

- Interior walls
- Suitable for use in dry conditions
- Kitchens



COVERAGE AT  
3MM THICKNESS



OPEN TIME



TILE TYPE



## Constraints

Not suitable for floors, exterior use or in wet areas such as bathrooms or showers. **weberfix WR** is recommended for such areas.

Not suitable for porcelain tiles. Not suitable for ceramic tiles larger than 30cm x 30cm.

For installation recommendations, including maximum weights and heights on substrates, please refer to the relevant BS 5385.

## Preparation

Ensure that all surfaces are clean, dry, sound and free from grease, dust or any other contaminating barrier and capable of supporting the weight of tiling.

Make good any unsound areas before tiling. Remove flaking or peeling layers.

Prime dusty or porous surfaces with **weber PR360** and allow to dry before tiling.

## Application

**Do not use at temperatures below 5°C.**

Spread the adhesive onto the wall, rather than onto the tiles, using a suitable notched trowel. Do not spread an area larger than can be tiled in approximately 30 minutes.

Studded-backed tiles may also need to be buttered with adhesive.

Fix the tiles within 30 minutes of applying adhesive (less at elevated temperatures). If lightly pressed, the adhesive should still stick to the fingers. If not, then it should be removed and more applied. Firmly press the tiles into the adhesive bed, with a twisting or sliding action, leaving at least 2mm gaps for grout joints.

The contact area between the adhesive and tile must be at least 70%, uniformly over the whole tile.

It is good practice to occasionally remove a tile to check that the required contact is being achieved.

Remove any excess adhesive from the tiles and joints before it sets.

## Wallboards; fibre/cement, plasterboard

A suitable board to receive tiling must be securely braced and fixed in accordance with the board manufacturers recommendations. Ensure the board is rigid and strong enough to support the expected load with only minimal deflection.

## Plaster

Tile onto a plaster finish coat. Leave new plaster for at least 4 weeks so that it will be strong enough to support the tiling weight. Priming with **weber PR360** is recommended. Plaster can support 20kg of tiling per m<sup>2</sup>.

## Cement/sand render

Leave new surfaces to dry for at least 2 weeks before tiling.

## Brickwork/blockwork

Leave new surfaces to dry for 6 weeks before tiling. Ensure that the surface is sufficiently flat. Lightweight blocks must be primed and are not suitable for large tiles.

## Allowance for movement

Flexible joints should be incorporated to allow for slight movements due to changes in temperature, humidity etc. as indicated by BS5385:

- where the tiling meets other materials (e.g. floor perimeters)
- along all internal corners – vertically and horizontally
- over existing movement joints or changes in background material

## Packaging

**weberfix plus** is supplied in 15kg plastic buckets.

## Coverage

Coverage depends on type of trowel and tile: from 2kg/m<sup>2</sup> in dry areas.

## Storage and shelf-life

When stored unopened in a dry place at temperatures above 5°C, shelf life is 12 months from date of manufacture.

## Health and safety

For further information, please request the Material Safety Data Sheet for this product.

## Technical data

Exceeds the requirements of BS EN 12004 for D1TE

Bed thickness	Up to 3mm
Coverage (approx.)	From 2kg/m <sup>2</sup> (dry areas)
Open time	30 minutes
Set time	24 hours
Temperature resistance	-10°C to 100°C when set

Note: setting times depend on temperature and humidity and also the tile size, substrate porosity and thickness of the adhesive bed.

**Saint-Gobain Weber**  
Dickens House, Enterprise Way,  
Maulden Road, Flitwick,  
Bedford, MK45 5BY  
 +44 (0) 1525 718877  
 [technical@netweber.co.uk](mailto:technical@netweber.co.uk)  
 [www.uk.weber](http://www.uk.weber)  
   @SGWeberUK

To the best of our knowledge and belief, this information is true and accurate, but as conditions of use and any labour involved are beyond our control, the end user must satisfy themselves by prior testing that the product is suitable for their specific application, and no responsibility can be accepted, or any warranty given by our Representatives, Agents or Distributors. Products are sold subject to our Standard Conditions of Sale and the end user should ensure that they have consulted our latest literature.

REV. 18/06/23